


TABLE OF CONTENTS

	Aguaizal abinglas			
	Aquaizol shingles	2		
	Roofing structure chart	3		
"Mosaic" series				
	"Standard" Collection	4	Brown ECO	13
	"Etalon" Collection	5	Sequoia	14
	Green Mix	6	Warm Wax	<u></u>
	Brown Mix	7	Mountain Canyon	16
	Red Mix	8	Alpine Meadow	17
	Morion	9	Fiery Lava	18
	Red ECO	10	Hawaiian Sand	19
	Green ECO	11	Red Poppy	20
	Cinnamon	12		
"Accent" series				
"Accent" series				
	"Standard" Collection	21	Sinai	30
	"Etalon" Collection	22	Cedar	31
	"Prestige" Collection	23	Marengo	32
	Red ECO	24	Graphite	33
	Mojito	25	Mountain Canyon	34
	Mexico	26	Persia	35
	Brown ECO	27	Whiskey	36
	Ripe Pomegranate	28	Hot Chocolate	37
	Morocco	29		
	Physical and mechanical properties	38	Notes	40
	Accessories for shingles and roofing	39		





Wide range and high quality of products as well as fair and affordable prices make it possible for our material to be a confident competitor in the world roofing market and to compete with the best manufacturers of shingles in the world.



Aquaizol shingles

Aquaizol shingles have the CE quality certificate and are manufactured in compliance with EN 544 requirements. The modern quality control system include management of all raw components, stages of production, packing and storage.


Aquaizol shingles are developed specifically for the purposes of being used in all climate conditions. These shingles are manufactured using only APP and SBS modified bitumen. Thus, they last longer and have better resistance against multiple temperature changes, wind pressure and precipitations.



Aquaizol shingles are:

- 100% leakproof
- Durability, 25/35/50-year guaranted lifespan
- · Wide spectrum of colors
- Convenient installation
- Light weight
- · Minimum waste with roofing of any complexity

- Noiselessness during hail and rain
- Fair price
- Availability of all accessories
- 100% corrosive resistant and rot-proof
- Appearance does not change with time




The entire line of Aquaizol shingles is represented by three collections. The "Standard" Collection comprises APP modified bitumen shingles with a 25-year guaranted lifespan, weight 8 kg/m². The "Etalon" Collection comprises APP modified bitumen shingles with a 35-year guaranted lifespan, weight 8 kg/m². The "Prestige" Collection comprises SBS modified bitumen shingles with a 50-year guaranted lifespan, weight 9,4 kg/m².





ROOFING STRUCTURE CHART

To install shingles, you will need galvanized roofing nails and Aquaizol cold bitumen mastic. You can find more information about the installation procedure for Aquaizol shingles on our website www.aquaizol.ua. We offer 34 types of Aquaizol shingles.




- 1 Attic window
- **2** Gutter
- 3 Storm water pipe
- 4 KP-1 eave trim
- 5 Fascia board
- 6 Aquaizol bitumen mastic
- 7 Aquaizol GF-1,5 underlay mat
- 8 Aquaizol GF-1,5 underlay mat
- 9 Flagon mat
- 10 Plank covering
- 11 Vent pipe opening
- 12 Aerator ridge
- 13 Aerator
- 14 Flagon mat upstand


- **15** PP-1 upstand plank
- 16 PT-1 end plank
- 17 Air gap in a solid base
- 18 Counter batten
- 19 Heat insulation
- 20 Roof tree
- 21 Vapor barries
- 22 Counter heat insulation
- 23 Metal wire (d=2 mm, step= 250 mm) or special mesh
- 24 Two layers of drywall
- 25 Apex tiles
- **26** Shingles
- 27 Cornice tiles

Shingles structure


Hydrophobic ceramising basaltic chips APP/SBS modified bitumen Reinforcing basis APP/SBS modified bitumen Self-adhesive layer Removable siliconized film



"MOSAIC" SERIES "STANDARD" COLLECTION



"MOSAIC" SERIES "ETALON" COLLECTION







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:






Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:








Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





COLOR: RED ECO



"MOSAIC" SERIES

Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package: APP modified

3 m² of roofing (22 shingles)









Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:



Specifications

Shingle dimensions: 1,0 x 0,32 m +115°C Heat resistance: Bitumen type: Package: APP modified

3 m² of roofing (22 shingles)









Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:








Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





COLOR: RED POPPY



"MOSAIC" SERIES

Specifications


Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:



"ACCENT" SERIES "STANDARD" COLLECTION









Red ECO Mojito Mexico Brown ECO

"ACCENT" SERIES "ETALON" COLLECTION



"ACCENT" SERIES "PRESTIGE" COLLECTION







Ripe Pomegranate

Marengo

Mountain Canyon



Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





COLOR: MEXICO



"ACCENT" SERIES

Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package: APP modified

3 m² of roofing (22 shingles)







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: APP modified

Bitumen type: APP modified
Package: 3 m² of roofing (22 shingles)





COLOR: RIPE POMEGRANATE



"ACCENT" SERIES

Specifications

Shingle dimensions: 1,0 x 0,32 m +115°C/+100°C Heat resistance: Bitumen type: Package:







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: APP modified

Package: 3 m² of roofing (22 shingles)



COLOR: SINAI



"ACCENT" SERIES

Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C/+100°C Bitumen type: APP/SBS modified Package: 3 m² of roofing (22 shingles)







Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:





Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C/+100°C Bitumen type: Package:









Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:



Specifications

Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:







Specifications


Shingle dimensions: 1,0 x 0,32 m Heat resistance: +115°C Bitumen type: Package:



PHYSICAL AND MECHANICAL PROPERTIES

Dimensions and shapes of single shingles, mm

1000



1000

Dimensions and Package	Shingles	Apex-cornice tiles	Underlay mat	Flagon mat
Length, mm	1000	1000	20 000	10 000
Width, mm	320	250	1000	1000
Polymer modificator type	APP/SBS	APP/SBS	APP	APP
Amount in a package	22 shingles (3 m²)	21 l.m of starter strip or 12 l.m of ridge cap	20 m²	10 m²
Weight, kg/m2	8,0/9,4	8,0/9,4	1,5	4,0
Weight bundle/roll,kg	24/28	23/27	30	40
Base	Glass-fiber	Glass-fiber	Glass-fiber/polyester	Polyester
Heat resistance	+115° C/+100° C	+115° C/+100° C	+90° C	+100° C

ACCESSORIES FOR SHINGLES AND ROOFING





Galvanized roofing nails



Underlay mat GF-1,5



Underlay mat PE-1,5



Apex-cornice tiles



Flagon mat



Special aerator



Ridge aerator



Eave trim



Upstand plank



End plank

You can find more information about the accessories as well as user's manuals by visiting our website www.aquaizol.ua.